

KEL-SNAP mounting frames

for tool-free snap-in mounting of cable entry frames / IP54 / UL Type 12




The patented KEL-SNAP frame provides a quick snap-in assembly of the KEL / KEL-U / KEL-QUICK / KEL-FG-A cable entry systems.

Control panels, cabinets or machines can be equipped with the KEL-SNAP frame at delivery, allowing a simple push in of the KEL frame when routing the cables and conduits. Perfect for enclosures that are maintenance intensive or for an install at a later date.

icotek is also offering the snap-in frame as splittable version KEL-SNAP-S in various sizes that makes a subsequent assembly possible.

There's also a blank plate BPK-SNAP available to close cut-outs of pre-assembled KEL-SNAP frames.

A cut-out of 46 mm also can be chosen instead of 36 mm. Thus prefabricated multi-pin connectors can be used.



Specifications

IP rating (EN 60529)	IP54
UL Type (UL 50E)	UL Type 12
Material	Polyamide
Flame class	UL94-V0, self-extinguishing
Operating temperature	-40 C° to 140 C°
Properties	silicone free, halogen free
Mounting options	Screw type mounting
height	38 mm

Advantages & benefits

- Upon disassembly (e.g. maintenance) screwing and unscrewing of the cable entry frame is not necessary
- Drilling template identical to cable entry frame (except KEL-SNAP-B)
- Integrated gasket
- Previously assembled cable harnesses are quickly and easily attached
- KEL-SNAP-S: Subsequent assembly possible
- KEL-SNAP-S: There is no need to thread the cables through the snap-on frame as the divisible frame can be snapped together when the lines have already been passed through the cut-out

Product types & sizes

KEL-SNAP 24



Part No.	42042
EAN	4251269307652
PU	10
Length	155 mm
Width	64 mm
Height	38 mm
Mounting height	38 mm

No. of screw holes	4
Diam. of screw holes	5,5 mm
Suitable for cable entry systems:	KEL 24, KEL-U 24, KEL-QUICK 24

KEL-SNAP 24-E



Part No.	42044
EAN	4251269307669
PU	1
Length	155 mm
Width	89 mm
Height	38 mm
Mounting height	38 mm

No. of screw holes	4
Diam. of screw holes	5,5 mm
Suitable for cable entry systems:	KEL 24-E

KEL-SNAP 24-MT

Part No. **42046**
 EAN **4251269307676**
 PU **1**
 Length **155 mm**
 Width **108 mm**
 Height **38 mm**
 Mounting height **38 mm**

No. of screw holes **6**
 Diam. of screw holes **5,5 mm**
 Suitable for cable entry systems: **KEL 24-MT**

KEL-SNAP 16

Part No. **42040**
 EAN **4251269307645**
 PU **10**
 Length **128 mm**
 Width **64 mm**
 Height **38 mm**
 Mounting height **38 mm**

No. of screw holes **4**
 Diam. of screw holes **5,5 mm**
 Suitable for cable entry systems: **KEL 16, KEL-U 16, KEL-QUICK 16**

KEL-SNAP 10

Part No. **42039**
 EAN **4251269307638**
 PU **10**
 Length **108 mm**
 Width **64 mm**
 Height **38 mm**
 Mounting height **38 mm**

No. of screw holes **4**
 Diam. of screw holes **5,5 mm**
 Suitable for cable entry systems: **KEL 10, KEL-U 10, KEL-QUICK 10**

KEL-SNAP-B

Part No. **42038**
 EAN **4251269307621**
 PU **10**
 Length **81 mm**
 Width **64 mm**
 Height **38 mm**
 Mounting height **38 mm**

No. of screw holes **4**
 Diam. of screw holes **5,5 mm**
 Suitable for cable entry systems: **KEL-B, KEL-U-B, KEL-QUICK-B**

KEL-SNAP-S 24

Part No. **42060**
 EAN **4251269323720**
 PU **10**
 Length **155 mm**
 Width **64 mm**
 Height **38 mm**
 Mounting height **38 mm**

No. of screw holes **4**
 Diam. of screw holes **5,5 mm**
 Suitable for cable entry systems: **KEL 24, KEL-U 24, KEL-QUICK 24**

KEL-SNAP-S 16

Part No. **42061**
 EAN **4251269323737**
 PU **10**
 Length **128 mm**
 Width **64 mm**
 Height **38 mm**
 Mounting height **38 mm**

No. of screw holes **4**
 Diam. of screw holes **5,5 mm**
 Suitable for cable entry systems: **KEL 16, KEL-U 16, KEL-QUICK 16**

KEL-SNAP-S 10

Part No. **42062**
EAN **4251269323744**
PU **10**
Length **108 mm**
Width **64 mm**
Height **38 mm**
Mounting height **38 mm**

No. of screw holes **4**
Diam. of screw holes **5,5 mm**
Suitable for cable entry systems: **KEL 10, KEL-U 10, KEL-QUICK 10**

KEL-SNAP-S-B

Part No. **42063**
EAN **4251269323751**
PU **10**
Length **81 mm**
Width **64 mm**
Height **38 mm**
Mounting height **38 mm**

No. of screw holes **4**
Diam. of screw holes **5,5 mm**
Suitable for cable entry systems: **KEL-B, KEL-U-B, KEL-QUICK-B**
