

# BPK-RF plastic blank plates

pluggable / IP54 / UL Type 12



BPK Blank plates seal cut-outs for standard 10-pole / 16-pole / 24-pole industrial connectors with IP rating IP54.

Blank plates are plugged into cut-outs (wall thickness from 1.5 to 3 mm).

IP54

UL TYPE  
12

UL  
US

RoHS  
compliant

REACH  
COMPLIANCE

Made in  
Germany

## Specifications

IP rating (EN 60529)	IP54
UL Type (UL 50E)	UL Type 12
Material	Polypropylene Integrated sealing lip: Elastomer
Flame class	UL94-V0, self-extinguishing
Operating temperature	-30 C° to 110 C°
Properties	silicone free, halogen free
Mounting options	Snap-in

## Advantages & benefits

- Fast mounting by snapping into the cut-out
- Integrated gasket

## Product types & sizes

### BPK 24-RF A



Part No.	42024.002
EAN	4251269307522
PU	10
Length	148 mm
Width	53 mm
Height	10,3 mm
Cut-out size	112 x 36 mm

For min. wall thickness	1,5 mm
For max. wall thickness	3 mm

### BPK 16-RF A



Part No.	42016.002
EAN	4251269307485
PU	10
Length	121 mm
Width	53 mm
Height	10,3 mm
Cut-out size	86 x 36 mm

For min. wall thickness	1,5 mm
For max. wall thickness	3 mm

---

**BPK 10-RF A**

Part No. **42015.002**  
EAN **4251269307461**  
PU **10**  
Length **101 mm**  
Width **53 mm**  
Height **10,3 mm**  
Cut-out size **65 × 36 mm**

For min. wall thickness **1,5 mm**  
For max. wall thickness **3 mm**

---

**BPK-B-RF A**

Part No. **42010.002**  
EAN **4251269307409**  
PU **10**  
Length **76 mm**  
Width **53 mm**  
Height **10,3 mm**  
Cut-out size **46 × 46 mm**

For min. wall thickness **1,5 mm**  
For max. wall thickness **3 mm**

---