

BPK plastic blank plates

for screw assembly / IP64 / UL Type 12



BPK Blank plates seal cut-outs for standard 10-pole / 16-pole / 24-pole industrial connectors with protection rating up to IP64 / UL type 12.

Blank plates are mounted via screws.

IP54

IP64

UL TYPE
12

UL
US

RoHS
compliant

REACH
COMPLIANCE

Made in
Germany

Specifications

IP rating (EN 60529)	IP54, IP64
UL Type (UL 50E)	UL Type 12
Material	Polypropylene Integrated sealing lip: Elastomer
Flame class	UL94-V0, self-extinguishing
Operating temperature	-30 C° to 110 C°
Properties	silicone free, halogen free
Mounting options	Screw type mounting

Advantages & benefits

■ Integrated gasket

Product types & sizes

BPK 24



Part No.	42024
EAN	4251269307515
PU	10
Length	148 mm
Width	53 mm
Height	10,3 mm
Max. cut-out length	112 mm


Max. cut-out width	36 mm
Cut-out size	112 x 36 mm
No. of screw holes	4
Diam. of screw holes	5,5 mm


BPK 16




Part No.	42016
EAN	4251269307478
PU	10
Length	121 mm
Width	53 mm
Height	10,3 mm
Max. cut-out length	86 mm

Max. cut-out width	36 mm
Cut-out size	86 x 36 mm
No. of screw holes	4
Diam. of screw holes	5,5 mm

BPK 10 	Part No.	42015	Max. cut-out width	36 mm
	EAN	4251269307454	Cut-out size	65 × 36 mm
	PU	10	No. of screw holes	4
	Length	101 mm	Diam. of screw holes	5,5 mm
	Width	53 mm		
	Height	10 mm		
	Max. cut-out length	65 mm		

BPK-B 	Part No.	42010	Max. cut-out width	46 mm
	EAN	4251269307393	Cut-out size	46 × 46 mm
	PU	10	No. of screw holes	4
	Length	76 mm	Diam. of screw holes	5,5 mm
	Width	53 mm		
	Height	10,3 mm		
	Max. cut-out length	46 mm		

BPK-JFX 	Part No.	42620	Diam. of screw holes	6,9 mm
	EAN	4251269309045		
	PU	5		
	Length	88 mm		
	Width	88 mm		
	Height	9 mm		
No. of screw holes	4			