ZL|SB-EMC shield plates

for strain relief plates



The shield plates ZL|SB-EMC provide shield earthing in addition to strain relief.

Affix the corresponding shield plates to ZL strain relief plates. The shield plate contacts the cable shield with the earth potential.

The result is a secure low resistance connection between cable shield and earth.

ZL strain relief plates offered separately.

Specifications

((<u>(</u>)) EN 61373

Material	Stainless steel
Mounting options	Screw type mounting

RoHS

Advantages & benefits

Product types & sizes

ZL 39|SB-EMC-1



 Part No.
 36322

 EAN
 4251269302541

 PU
 10

 For max. no. of cables
 3

 Length L1
 42 mm

 Length L2
 19,5 mm

 Width
 26 mm

 Height
 12 mm

 No. of screw holes
 2

 Diam. of screw holes
 6,5 mm

 No. of teeth
 3

ZL 39|SB-EMC-2



 Part No.
 37150

 EAN
 4251269305221

 PU
 10

 For max. no. of cables
 3

 Length L1
 42 mm

 Length L2
 19,5 mm

 Width
 42,1 mm

 Height
 12 mm

 No. of screw holes
 2

 Diam. of screw holes
 6,5 mm

 No. of teeth
 3

ZL 60|SB-EMC-1



 Part No.
 36328

 EAN
 4251269302572

 PU
 10

 For max. no. of cables
 4

 Length L1
 64 mm

 Length L2
 43,5 mm

 Width
 26 mm

 Height
 12 mm

 No. of screw holes
 2

 Diam. of screw holes
 6,5 mm

 No. of teeth
 4

ZL 60|SB-EMC-2



Part No. EAN PU

For max. no. of cables

Length L1 Length L2 Width 37152

4251269305238

10 4 64 mm 43,5 mm 42,1 mm Height

No. of screw holes
Diam. of screw holes

No. of teeth

12 mm

2

6,5 mm

ZL 87|SB-EMC-1



Part No. EAN

PU

For max. no. of cables

Length L1 Length L2 Width 36324

10

4251269302558

6 90 mm 68 mm 26 mm Height

No. of screw holes Diam. of screw holes

No. of teeth

12 mm

2

6,5 mm

ZL 87|SB-EMC-2



Part No. EAN

PU

For max. no. of cables

Length L1 Length L2 Width 37154

4251269305245

6 90 mm 68 mm 42,1 mm Height

No. of screw holes Diam. of screw holes

No. of teeth

12 mm

2 6,5 mm

6

ZL 103|SB-EMC-1



Part No.

EAN PU

For max. no. of cables

Length L1 Length L2 Width 36332

4251269302596

26 mm

Height

No. of screw holes Diam. of screw holes

No. of teeth

12 mm

2 6,5 mm

7

ZL 103|SB-EMC-2



Part No.

EAN PU

For max. no. of cables

Length L1 Length L2 Width 37156

4251269305252

10

7 106 mm 84 mm 42,1 mm Height

No. of screw holes Diam. of screw holes

No. of teeth

12 mm

6,5 mm

7

ZL 121|SB-EMC-1



Part No.

EAN PU

For max. no. of cables

Length L1 Length L2 Width 36330

4251269302589

10 8 124 mm 102,5 mm

26 mm

Height

No. of screw holes Diam. of screw holes No. of teeth 12 mm

2 6.5 mm

6,5 mm

3

ZL 121|SB-EMC-2



Part No. EAN

PU

For max. no. of cables

Length L1 Length L2 Width 37158 4251269305269

10 8 124 mm 102,5 mm

42,1 mm

Height

No. of screw holes Diam. of screw holes

No. of teeth

12 mm

2 6,5 mm

ZL 140|SB-EMC-1



Part No.

EAN PU

For max. no. of cables

Length L1 Length L2 Width 36326

4251269302565

Height

No. of screw holes Diam. of screw holes

No. of teeth

12 mm

2

6,5 mm

ZL 140|SB-EMC-2



Part No.

EAN PU

For max. no. of cables Length L1

Length L2 Width 37159

4251269305276

10 9 142 mm 121 mm 42,1 mm Height

No. of screw holes Diam. of screw holes

No. of teeth

12 mm

2

6,5 mm